



**Village of Pawling
Building Department**

**9 Memorial Avenue
Pawling, New York 12564**

Telephone (845) 855-1128
Fax (845) 855-9317
www.villageofpawling.org
Email: bldgsecy@villageofpawling.org

**Truss Type,
Pre-Engineered Wood
or Timber Construction**

RESIDENTIAL & COMMERCIAL STRUCTURES

FOR OFFICE USE ONLY

APPLICATION NO. _____

DATE RECEIVED: _____

Project Location:

TAX MAP SECTION _____ STREET / ADDRESS _____ VILLAGE _____
BLOCK _____ LOT _____

OWNER INFORMATION:

NAME: _____

MAILING ADDRESS: _____

TELEPHONE # _____

E-MAIL: _____

PLEASE TAKE NOTICE THAT THE STRUCTURE IS (CHECK EACH APPLICABLE LINE):

- ☐ NEW STRUCTURE ☐ ADDITION TO EXISTING STRUCTURE
☐ EXISTING STRUCTURE ☐ REHABILITATION TO EXISTING STRUCTURE

**TO BE CONSTRUCTED OR PERFORMED AT THE SUBJECT PROPERTY REFERENCE ABOVE WILL UTILIZE
(CHECK EACH APPLICABLE LINE): (see back for sign designation)**

- ☐ TRUSS TYPE CONSTRUCTION (TT) ☐ PRE-ENGINEERED WOOD CONSTRUCTION (PW)
☐ TIMBER CONSTRUCTION FLOOR (TC) ☐ OTHER: _____

IN THE FOLLOWING LOCATION(S) (CHECK EACH APPLICABLE LINE): (see back for sign designation)

- ☐ FLOOR FRAMING, INCLUDING GIRDERS AND BEAMS (F) ☐ ROOF FRAMING (R)
☐ FLOOR FRAMING AND ROOF FRAMING (FR) ☐ OTHER: _____

STRUCTURE CONSTRUCTION TYPE: (CHECK APPLICABLE LINE): (see back for sign designation)

- ☐ TYPE I NONCOMBUSTIBLE ☐ TYPE III NONCOMBUSTIBLE EXTERIOR WALLS ☐ TYPE V (COMBUSTIBLE)
OR ANY MATERIAL
☐ TYPE II NONCOMBUSTIBLE ☐ TYPE IV HEAVY TIMBER PERMITTED BY CODE

Application is hereby made to the Village of Pawling Building Department for the issuance of a Building Permit for construction as herein described, pursuant to provisions of the Code of the Village of Pawling. The owner and the applicant hereby agree to comply with all applicable laws, ordinances and regulations and with all regulations and procedures as explained in this application, and will allow all inspectors to enter the premises for all required and necessary inspections.

OWNER OR OWNER'S REPRESENTATIVE SIGNATURE

DATE

OWNER OR OWNER'S REPRESENTATIVE PRINT

IDENTIFICATION OF BUILDINGS UTILIZING TRUSS TYPE CONSTRUCTION (check appropriate symbol)

	TYPE I NONCOMBUSTIBLE	TYPE II NONCOMBUSTIBLE	TYPE III NONCOMBUSTIBLE EXTERIOR WALLS	TYPE IV HEAVY TIMBER	TYPE V ANY MATERIAL PERMITTED BY	
Floor Construction						Floor Construction
Roof Construction						Roof Construction
Floor & Roof Construction						Floor & Roof Construction

Required Sign Location(s)

Residential Construction

Affixed to electric meter box attached to the exterior of the structure or affixed to the exterior wall of the residential structure at a point immediately adjacent to the electric box or a location likely to be seen by first responders with approval by the authority having jurisdiction.

The construction type designation shall be "I", "II", "III", "IV" or "V" to indicate the construction classification of the structure under section 602 of the BCNYS

DESIGNATION FOR STRUCTURAL COMPONENTS THAT ARE OF TRUSS TYPE CONSTRUCTION

"F"	FLOOR FRAMING, INCLUDING GIRDERS AND BEAMS
"R"	ROOF FRAMING
"FR"	FLOOR AND ROOF FRAMING

NYS BUILDING STANDARDS AND CODES

Commercial Construction

Exterior building entrance doors, exterior exit discharge doors, and exterior roof access doors to a stairway	Attached to the door, or attached to a sidelight or the face of the building, not more than 12 inches (305 mm) horizontally from the latch side of the door jamb, and not less than 42 inches (1067 mm) nor more than 60 inches (1524 mm) above the adjoining walking surface.
Exterior building entrance doors, exterior exit discharge doors, and exterior roof access doors to a stairway	Attached at each end of the row of doors and at a maximum horizontal distance of 12 feet (3.65M) between signs, and not less than 42 inches (1067 mm) nor more than 60 inches (1524 mm) above the adjoining walking surface.
Fire department hose connections	Attached to the face of the building, not more than 12 inches (305 mm) horizontally from the center line of the fire department hose connection, and not less than 42 inches (1067 mm) nor more than 60 inches (1524 mm) above the adjoining walking surface.

DESIGNATION FOR STRUCTURAL COMPONENTS THAT ARE OF TRUSS CONSTRUCTION